

**Honeywell Pressure reducing  
valve brass 1 1/4" male thread  
16bar 0,16 mm DN32 stainless  
steel DVGW/KIWA/WRAS type  
D06F (0410932)**



**Honeywell**

# TECHNICAL SPECIFICATIONS

|                         |                       |
|-------------------------|-----------------------|
| Type                    | D06F                  |
| Material                | brass                 |
| Approval                | DVGW/KIWA/WRAS        |
| Material filter element | stainless steel       |
| Membrane material       | NBR                   |
| Material housing        | brass                 |
| Material seal           | NBR                   |
| Connection              | male thread           |
| Filtration              | 0,16 mm               |
| Factory pre-adjustment  | 3 bar                 |
| Outlet pressure         | 1,5 - 6 bar           |
| Pressure                | 16 bar                |
| Max. temp.              | 40 °C                 |
| Capacity                | 5,9 m <sup>3</sup> /h |
| Size                    | 1 1/4"                |
| Length                  | 200 mm                |
| DN                      | 32                    |

Weight

2 kg

Height

175 mm

## PRODUCT INFORMATION

Comes without pressure gauge.

**Last modified date: 04/11/2025**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>