

Pentair Sand filter fibreglass reinforced polyester 2" female thread 2,5bar blue type Triton® F-36S8-NEO-CP (7021213)



TECHNICAL SPECIFICATIONS

Colour	blue
Material	fibreglass reinforced polyester
Connection	female thread
Pressure	2,5 bar
Max. temp.	50 °C
Type	Triton® F-36S8-NEO-CP
Capacity	32 m ³ /h
Gravel	100 kg
Size	2"
Diameter	914 mm
Weight	35.5 kg
Sand	300 kg
Filter area	0.64 m ²
Max flow rate	32 m ³ /h
Max. pool vol.	160 m ³

DIMENSIONS


B	36 " inch
---	-----------

A	1160 mm
---	---------

B	914 mm
---	--------

C	738 mm
---	--------

D	657 mm
---	--------



PRODUCT INFORMATION

One-piece, fibreglass-reinforced tank with UV-resistant coating.

With side-mount 6-way valve.

Switch off the pump before each lever action.

Warranty period: Tank 10 years

Last modified date: 06/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>