

**Bermad Solenoid valve  
fibreglass reinforced nylon  
3/4" female thread 10bar  
24VAC black type 200 without  
flow control (7033089)**



# TECHNICAL SPECIFICATIONS

|                        |                             |
|------------------------|-----------------------------|
| Colour                 | black                       |
| Type                   | 200                         |
| Material               | fibreglass reinforced nylon |
| Operation              | indirect solenoid-operated  |
| Membrane material      | NBR                         |
| Indirect effect        | yes                         |
| Seat material          | NBR                         |
| Material housing       | fibreglass reinforced nylon |
| Material seal          | NBR                         |
| Connection             | female thread               |
| Right-angled model     | no                          |
| Type                   | without flow control        |
| Minimum inlet pressure | 0.7 bar                     |
| Pressure               | 10 bar                      |
| Max. temp.             | 50 °C                       |
| Capacity               | 150 l/min                   |
| Size                   | 3/4"                        |

Voltage

24VAC

**Last modified date: 08/11/2025**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>