

**DAB Submersible borehole
pump stainless steel 304 1 1/4"
female thread 6,3A 230VAC
with 30m cable and control box
booster type S4 KIT 3/13 oil
cooling (7030914)**



TECHNICAL SPECIFICATIONS

Material stainless steel 304

Pump body stainless steel 304

Material impeller 1 technopolymer

Connection female thread

Type oil cooling

Voltage 230VAC

Max. temperature 40 °C

Outer ø 99 mm

Minimum medium temperature 0 °C
(continuous)

Maximum ambient temperature -10 °C

Minimum ambient temperature 40 °C

IP value IP68, class F

Type S4 KIT 3/13

Output Power 1 HP

Model with 30m cable and control box booster

MWC 72 m

Size	1 1/4"
Weight	12.9 kg
Power	0.75 kW
Impellers	13
Ampere	6,3 A
Max flow rate	4.2 m ³ /h
Press	1 "
BEP Capacity	3.47
BEP Head	42.5
PORlh	57.1
PORhh	29.8
PORlq	2.4
PORhq	4.2
Efficiency	63,7 %
Packaging dimensions L/W/H	120 x 120 x 1006 mm

DIMENSIONS

Db	99 mm
H-1	906 mm

ØDi-1

1 1/4 "



PRODUCT INFORMATION

Submersible borehole pump kit with pump body and motor, power supply cable, cord and control box.

Pump maximum diameter: 99 mm

Maximum amount of sand: 150 g/m³

Installation: Fixed in vertical position or horizontal installation with a cooling sleeve.

Motor: 4OL oil-filled two-pole asynchronous DAB motor

Last modified date: 08/05/2026

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E enquiries@bosta.co.uk

<http://www.bosta.com>