

**DAB Deep well pump stainless steel 304 2" female thread 10,8A 230VAC with 15m cable and control box booster type S4 KIT 8/9 oil cooling (7030920)**



# TECHNICAL SPECIFICATIONS

Material stainless steel 304

Pump body stainless steel 304

Material impeller 1 technopolymer

Connection female thread

Type oil cooling

Voltage 230VAC

Max. temperature 40 °C

Outer ø 99 mm

Minimum medium temperature 0 °C  
(continuous)

Maximum ambient temperature -10 °C

Minimum ambient temperature 40 °C

IP value IP68, class F

Type S4 KIT 8/9

Output Power 2 HP

Model with 15m cable and control box booster

Size 2"



Weight	16.8 kg
Power	1.5 kW
Impellers	9
MWC	54
Ampere	10,8 A
Max flow rate	10.8 m <sup>3</sup> /h
Press	2 "
BEP Capacity	7.2
BEP Head	45.5
PORlh	54.6
PORhh	31.9
PORlq	8.6
PORhq	5
Efficiency	65,2 %
Packaging dimensions L/W/H	120 x 120 x 1131 mm

## DIMENSIONS

H-1	1031 mm
ØDi-1	2 "

Db

99 mm



# PRODUCT INFORMATION

Deep well pump kit with pump body and motor, power supply cable, cord and control box.

Pump maximum diameter: 99 mm

Maximum amount of sand: 150 g/m<sup>3</sup>

Installation: Fixed in vertical position or horizontal installation with a cooling sleeve.

Motor: 4OL oil-filled two-pole asynchronous DAB motor

**Last modified date: 08/11/2025**

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)

<http://www.bosta.com>