

**DAB Submersible pump
reinforced plastic 1 1/4" male
thread 3,5A 230VAC green
type Nova UP 600 M-AE
(7030948)**



TECHNICAL SPECIFICATIONS

Colour	green
Material	reinforced plastic
Pump body	technopolymer
Material impeller 1	technopolymer
Connection	male thread
Float	integrated
Voltage	230VAC
Max. temperature	35 °C
Minimum medium temperature (continuous)	0 °C
Press	1 1/4 "
Maximum ambient temperature	40 °C
Minimum ambient temperature	0 °C
Type	Nova UP 600 M-AE
Output Power	0,69 HP
MWC	9,8 m
Size	1 1/4"

Power 0.52 kW

Ampere 3,5 A

Max flow rate 13.5 m³/h

BEP Capacity 10.8

BEP Head 5.74

PORlh 7.17

PORhh 4.47

PORlq 7.56

PORhq 12.96

DIMENSIONS



Db 160 mm

H-1 111.6 mm

H-2 324 mm

W-1 206 mm

ØDi-1 1 "



PRODUCT INFORMATION

Installation: vertical, fixed or portable. Max. immersion depth: 7 metres.

Pump can be used with liquids containing solid particles of up to 10 mm in size.

Suited for narrow well installation requiring automatic suction up to 2/3 mm. Filter is removable.

Dry operation of max. 1 minute.

Last modified date: 08/05/2026

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E enquiries@bosta.co.uk

<http://www.bosta.com>