

**Rain Bird Solenoid valve  
fibreglass reinforced nylon 2"  
female thread 13.8bar 24VAC  
black type PESB (7021688)**



**RAIN BIRD**

# TECHNICAL SPECIFICATIONS

|                        |                                                     |
|------------------------|-----------------------------------------------------|
| Colour                 | black                                               |
| Type                   | PESB                                                |
| Material               | fibreglass reinforced nylon                         |
| Operation              | indirect solenoid-operated with flow control handle |
| Material housing       | glass-filled nylon                                  |
| Connection             | female thread                                       |
| Pressure               | 13.8 bar                                            |
| Max. temp.             | 66 °C                                               |
| Capacity               | 750 l/min                                           |
| Size                   | 2"                                                  |
| Voltage                | 24VAC                                               |
| Frequency              | 50 Hz                                               |
| Minimum inlet pressure | 1.4 bar                                             |

## PRODUCT INFORMATION

The PESB solenoid valve is tough and reliable for all applications, even dirty water applications used for ponds rivers and wells.

The PESB solenoid valve is compatible with the Rain Bird irrigation decoders, and with the PRS

pressure regulator.

The PESB solenoid valve contains a scrubber, which filters dirty water very efficiently.

**Last modified date: 06/11/2025**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>