

**3-way ball valve T-bore PVC-U  
50 mm glue socket 10bar DN40  
grey type T-bore side  
connection (0111523)**



# TECHNICAL SPECIFICATIONS

|        |      |
|--------|------|
| Colour | grey |
|--------|------|

|      |        |
|------|--------|
| Type | T-bore |
|------|--------|

|          |       |
|----------|-------|
| Material | PVC-U |
|----------|-------|

|           |       |
|-----------|-------|
| Operation | lever |
|-----------|-------|

|              |     |
|--------------|-----|
| Colour lever | red |
|--------------|-----|

|                 |       |
|-----------------|-------|
| Handle material | PVC-U |
|-----------------|-------|

|                  |       |
|------------------|-------|
| Material housing | PVC-U |
|------------------|-------|

|               |           |
|---------------|-----------|
| Material seal | PTFE/EPDM |
|---------------|-----------|

|           |        |
|-----------|--------|
| Ball bore | T-bore |
|-----------|--------|

|                 |                 |
|-----------------|-----------------|
| Connection type | side connection |
|-----------------|-----------------|

|            |             |
|------------|-------------|
| Connection | glue socket |
|------------|-------------|

|                   |            |
|-------------------|------------|
| Temperature range | 0°C - 60°C |
|-------------------|------------|

|          |        |
|----------|--------|
| Pressure | 10 bar |
|----------|--------|

|       |     |
|-------|-----|
| Shaft | PVC |
|-------|-----|

|      |       |
|------|-------|
| Size | 50 mm |
|------|-------|

|    |    |
|----|----|
| DN | 40 |
|----|----|

# DIMENSIONS

Lb 207 mm

ØDi-1 50 mm

ØDi-2 50 mm

Ct-1 94 mm

R 128 mm

ØDf 40 mm



**Last modified date: 30/10/2025**

Bosta UK Ltd.  
Reflection House  
Olding Road

Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>