

**DAB Submersible borehole
pump stainless steel 304 1 1/4"
female thread 4,5A 230VAC
with 15m cable and control box
booster type S4 KIT 2/10 oil
cooling (7030912)**



TECHNICAL SPECIFICATIONS

Material stainless steel 304

Pump body stainless steel 304

Material impeller 1 technopolymer

Connection female thread

Type oil cooling

Voltage 230VAC

Max. temperature 40 °C

Outer ø 99 mm

Minimum medium temperature 0 °C
(continuous)

Maximum ambient temperature -10 °C

Minimum ambient temperature 40 °C

IP value IP68, class F

Type S4 KIT 2/10

Output Power 0,75 HP

Model with 15m cable and control box booster

MWC 67 m

Size	1 1/4"
Weight	10.9 kg
Power	0.55 kW
Impellers	10
Ampere	4,5 A
Max flow rate	3 m ³ /h
Press	1 "
BEP Capacity	2.15
BEP Head	46.1
PORlh	56.3
PORhh	37
PORlq	1.5
PORhq	2.6
Efficiency	57,2 %
Packaging dimensions L/W/H	120 x 120 x 826 mm

DIMENSIONS

Db	99 mm
H-1	726 mm

ØDi-1

1 1/4 "



PRODUCT INFORMATION

Submersible borehole pump kit with pump body and motor, power supply cable, cord and control box.

Pump maximum diameter: 99 mm

Maximum amount of sand: 150 g/m³

Installation: Fixed in vertical position or horizontal installation with a cooling sleeve.

Motor: 4OL oil-filled two-pole asynchronous DAB motor

Last modified date: 08/05/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>