

# Ball valve PVC-U 75 mm glue socket 10bar DN65 grey type AK (0161506)



# TECHNICAL SPECIFICATIONS

|        |      |
|--------|------|
| Colour | grey |
|--------|------|

|      |    |
|------|----|
| Type | AK |
|------|----|

|          |       |
|----------|-------|
| Material | PVC-U |
|----------|-------|

|           |       |
|-----------|-------|
| Operation | lever |
|-----------|-------|

|              |     |
|--------------|-----|
| Colour lever | red |
|--------------|-----|

|                 |       |
|-----------------|-------|
| Handle material | PVC-U |
|-----------------|-------|

|                      |        |
|----------------------|--------|
| Housing construction | 3-part |
|----------------------|--------|

|                  |       |
|------------------|-------|
| Material housing | PVC-U |
|------------------|-------|

|               |         |
|---------------|---------|
| Material seal | PE/EPDM |
|---------------|---------|

|            |             |
|------------|-------------|
| Connection | glue socket |
|------------|-------------|

|                  |       |
|------------------|-------|
| Max. temperature | 60 °C |
|------------------|-------|

Minimum medium temperature 0 °C  
(continuous)

|      |       |
|------|-------|
| Size | 75 mm |
|------|-------|

|    |    |
|----|----|
| DN | 65 |
|----|----|

|          |        |
|----------|--------|
| Pressure | 10 bar |
|----------|--------|

# DIMENSIONS

Lb 238 mm

ØDi-1 75 mm

ØDi-2 75 mm

Ct-1 184 mm

R 100 mm

ØDf 65 mm



**Last modified date: 31/10/2025**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds

Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>