

**Itap Foot valve brass 2 1/2"
female thread 6bar DN65 type
140 with stainless steel 304
strainer (7038944)**



TECHNICAL SPECIFICATIONS

| | |
|------|---------------------------------------|
| Type | 140 with stainless steel 304 strainer |
|------|---------------------------------------|

| | |
|----------|-------|
| Material | brass |
|----------|-------|

| | |
|----------------|-------|
| Material valve | brass |
|----------------|-------|

| | |
|------------------|-------|
| Material housing | brass |
|------------------|-------|

| | |
|---------------|-----|
| Material seal | NBR |
|---------------|-----|

| | |
|------------|---------------|
| Connection | female thread |
|------------|---------------|

| | |
|-------------------|------------|
| Temperature range | 0°C - 90°C |
|-------------------|------------|

| | |
|------|--------|
| Size | 2 1/2" |
|------|--------|

| | |
|--------|--------|
| Length | 168 mm |
|--------|--------|

| | |
|----|----|
| DN | 65 |
|----|----|

| | |
|---------|--------|
| Outer ø | 100 mm |
|---------|--------|

| | |
|----------|-------|
| Pressure | 6 bar |
|----------|-------|

PRODUCT INFORMATION

The Brass foot valve, type 140 is made from brass and contains a stainless steel 304 strainer. It is mostly used by professionals in agricultural and industrial applications. The check valve can only be installed vertically. It is available in a wide range of Female BSP thread connection with a working pressure up to 10 bar.

Last modified date: 09/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>