

**DAB Multi-stage centrifugal
pump stainless steel 304 1"
female thread 8bar 5,3A
230VAC green self priming
type EUROINOX 30/80M
(7030923)**



TECHNICAL SPECIFICATIONS

Colour	green
Material	stainless steel 304
Material impeller 1	technopolymer
Model	self priming
Connection	female thread
Voltage	230VAC
Max. temperature	35 °C
Width	174 mm
Minimum medium temperature (continuous)	0 °C
Height	203 mm
Press	1 "
Maximum ambient temperature	40 °C
Suction	1 "
Minimum ambient temperature	0 °C
Type	EUROINOX 30/80M
Output Power	1,1 HP



Size	1"
Length	458 mm
Weight	14.8 kg
Power	0.8 kW
MWC	47
Max flow rate	7.2 m ³ /h
BEP Capacity	5.4
BEP Head	27.1
Packaging dimensions L/W/H	480 x 212 x 265 mm

DIMENSIONS

Cb-1	143 mm
Cl-1	166 mm
G-1	111 mm
H-1	203 mm
L	458 mm
Mr	241 mm
O	9 mm
W-1	174 mm

ØDi-1 1 "

ØDi-2 1 "



PRODUCT INFORMATION

Installation: fixed or portable in a horizontal position.

Supplied without cable, installation should be done by a qualified electrician.

Last modified date: 26/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>