

**Rain Solenoid valve fibreglass  
reinforced nylon 3" female  
thread 10bar 24VAC black type  
RN180 (0862908)**



# TECHNICAL SPECIFICATIONS

|                             |                             |
|-----------------------------|-----------------------------|
| Colour                      | black                       |
| Material                    | fibreglass reinforced nylon |
| Operation                   | indirect servo-operated     |
| Indirect effect             | yes                         |
| Material housing            | fibre-reinforced plastic    |
| Material seal               | NBR                         |
| Connection                  | female thread               |
| Right-angled model          | no                          |
| Temperature range           | 4°C - 70°C                  |
| Minimum pressure difference | 1 bar                       |
| Frequency                   | 50 Hz                       |
| Minimum inlet pressure      | 1 bar                       |
| Pressure                    | 10 bar                      |
| Direct current (DC)         | no                          |
| Type                        | RN180                       |
| Capacity                    | 1200 l/min                  |
| Size                        | 3"                          |

Voltage

24VAC

## PRODUCT INFORMATION

The plastic electric valve is for hobby or professional use.

Technical Specification:

Temperature-resistant from 4° to 70°C.

All types with flow control and manual operation.

**Last modified date: 05/11/2025**

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)

<http://www.bosta.com>