

# NaanDan Button dripper plastic 4/7 mm push-in x barbed 2,0ltr/h brown/green type Click Tif, PC (7026015)



**NaanDan**  
by Rivulis

# TECHNICAL SPECIFICATIONS

Type	Click Tif, PC
Material	plastic
Connection	push-in x barbed
Opening pressure	0,8 - 0,3 bar
Rec. press.	1 - 4 bar
Colour	brown/green
Flow	2,0 ltr/h
Size	4/7 mm

## PRODUCT INFORMATION

Click Tif PC (Pressure Compensated) on-line button dripper. Pressure Regulating Range: 0.5 - 4.0 bar; Minimum Working Pressure: 1.0 bar. Minimum pressure at lateral end: 0.5 bar; Lateral Length exceeding 800m is not recommended. Recommended filtration: 130 micron. For fitting into PE40 pipe, punch 3mm hole. Coefficient of manufacturing Variation (CV): 3%. Application: ideal dripper for crops in uneven terrains where pressure differences are too big and using the CNL type is not possible due to its opening/closing pressure range. The PC type will open at lower pressure and keep open at higher pressures.

**Last modified date: 06/11/2025**

Bosta UK Ltd.  
Reflection House  
Olding Road

Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>