

**DAB Submersible pump
stainless steel 304 2" female
thread 1,64A 380VAC stainless
steel type Feka VS 550 T-NA
(7043951)**



TECHNICAL SPECIFICATIONS

Colour	stainless steel
--------	-----------------

Material	stainless steel 304
----------	---------------------

Pump body	stainless steel 304
-----------	---------------------

Material impeller 1	stainless steel 304
---------------------	---------------------

Connection	female thread
------------	---------------

Max. temperature	50 °C
------------------	-------

Minimum medium temperature 0 °C (continuous)	
---	--

Press	2 "
-------	-----

Maximum ambient temperature 40 °C	
-----------------------------------	--

Minimum ambient temperature 0 °C	
----------------------------------	--

Type	Feka VS 550 T-NA
------	------------------

Size	2"
------	----



Float	not included
-------	--------------

Voltage	380VAC
---------	--------

Ampere	1,64 A
--------	--------

DIMENSIONS

Cb-1	98 mm
Db	170 mm
H	172 mm
L	492 mm
W-1	203 mm
ØDi-1	2 "



PRODUCT INFORMATION

Power cable: 10 metre H07RN-F, with plug for the single-phase version.

Installation: fixed or portable, vertical position.

Maximum immersion depth: 7 metre

Suitable for residential waste water as sewage containing solid matter with size up to 50 mm.

Last modified date: 05/09/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>