

**NaanDan Dripper set plastic 4 mm x 4/7 mm push-in x barbed 4ltr/h 60cm white type Click Tif, PC CNL (7020672)**



**NaanDan**  
by Rivulis

# TECHNICAL SPECIFICATIONS

Colour	white
Type	Click Tif, PC CNL
Material	plastic
Connection	push-in x barbed
Opening pressure	0,8 - 0,3 bar
Rec. press.	1 - 4 bar
Flow	4 ltr/h
Size	4 mm x 4/7 mm
Length	60 cm

## PRODUCT INFORMATION

The ClickTif CNL (Compensated Non-Leakage) on-line button dripper prevents the system from draining which reduces the filling time of the system and allows all plants to receive the same amount of water.

Opening Pressure: 0.8 bar.

Closing Pressure: 0.3 bar.

Pressure Regulating Range: 0.5 - 4.0 bar; Minimum Working Pressure: 1.0 bar.

Minimum pressure at lateral end: 0.8 bar; Lateral Length exceeding 800m is not recommended.

For fitting into PE40 pipe, punch 3mm hole.

Recommended filtration: 130 micron.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal for pulse irrigation in crops growing in tunnels or greenhouses such as strawberries, peppers, tomato, cucumber, raspberries, eggplants, etc.

## Last modified date: 06/11/2025

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>