

**Profec Butterfly valve ductile
iron (GGG40) epoxy coating
DN250 flange 10bar DN250
blue PN6/10/16 type 601 disc
stainless steel 316 (0401872)**



TECHNICAL SPECIFICATIONS

Colour	blue
Type	601
Material	ductile iron (GGG40)
Surface treatment	epoxy coating
Operation	lever
Colour lever	black
Handle material	malleable cast iron
Material valve	stainless steel 304
Material spindle	stainless steel 316
Seat material	EPDM
Material housing	ductile iron (GGG40)
Material seal	EPDM
Connection	flange
DIN Standard	DIN 2501
Flange	PN6/10/16
Temperature range	0°C - 90°C
Pressure	10 bar

Size DN250

DN 250

Width 66 mm

Height 542 mm

Torque 300 Nm

DIMENSIONS

Construction length din 3202 k1, iso 5752


W-1 66 mm

PCD 335/355 mm

Ct-1 330 mm

R 360 mm

W-2 132 mm



Last modified date: 04/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>