

Profec Ball valve PVC-U 32 mm glue socket 16bar DN25 grey type Safe 600 (0112103)



TECHNICAL SPECIFICATIONS

Colour	grey
--------	------

Type	Safe 600
------	----------

Material	PVC-U
----------	-------

Operation	lever
-----------	-------

Colour lever	red
--------------	-----

Handle material	PVC-U
-----------------	-------

Housing construction	3-part
----------------------	--------

Ball material	PVC-U
---------------	-------

Material spindle	PVC-U
------------------	-------

Material housing	PVC-U
------------------	-------

Material seal	hytrel/EPDM
---------------	-------------

Connection	glue socket
------------	-------------

Max. temperature	60 °C
------------------	-------

Minimum medium temperature 0 °C
(continuous)

Pressure	16 bar
----------	--------

Size	32 mm
------	-------

DN

25

DIMENSIONS

Ct-1 71 mm


Lb 126 mm

R 54 mm

ØDf 25 mm

ØDi-1 32 mm

ØDi-2 32 mm



PRODUCT INFORMATION

With secure ball.

Last modified date: 04/09/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>