

Hunter Pop-up sprinkler plastic 1" female thread 50°-360° black type I-25-04 (7026274)



Hunter®

TECHNICAL SPECIFICATIONS

Colour black

Material plastic

Capacity 0,82 - 7,24 m³/h

Capacity 13,6 - 120,2 l/min

Connection female thread

Sector adj. range 50°-360°

Angle 25 °

Max diameter 43.2 m

Radius 11,9 - 21,6 m

Rec. press. 2,5 - 7 bar

Type I-25-04

Size 1"

Riser height 10 cm

Type I-40														
Nr.41			Nr.42			Nr.43			Nr.44			Nr.45		
Bar	Q	R	Bar	Q	R	Bar	Q	R	Bar	Q	R	Bar	Q	R
3,5	2,32	13,4	3,5	2,50	14,0	3,5	3,23	15,5	4,0	4,54	17,7	4,0	5,00	18,3
4,0	2,61	13,4	4,0	2,80	14,3	4,0	3,52	15,8	5,0	4,95	17,7	5,0	5,52	19,0
5,0	2,86	13,7	5,0	3,07	14,9	5,0	3,70	15,8	5,5	5,41	18,3	5,5	5,88	19,5
5,5	3,07	14,0	5,5	3,27	15,2	5,5	4,11	16,2	6,0	5,66	18,3	6,0	6,25	19,8

PRODUCT INFORMATION

The Hunter I-25 Strong as iron. That's the I-25 sprinkler. As it has an irrigation radius of 12 to 21 metres, this rotor can be used in zones of different sizes. Playing fields, lawns, flowerbeds: no project is too much. Its compact design can be supplied with an optional stainless steel riser. The I-25 is a reliable, strong and sustainable choice. Let the Hunter I-25 do the hard work for you, day in, day out. Now there's no need for you to do it.

Last modified date: 05/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>