

**Yamit Sand filter carbon steel  
ST37.2 epoxy coating 48"  
Victaulic 8bar DN100 blue type  
F660 (7024317)**



**YAMIT**  
FILTRATION

# TECHNICAL SPECIFICATIONS

Colour	blue
Material	carbon steel ST37.2
Connection	Victaulic
Pressure	8 bar
Type	F660
Capacity	55 - 79 m <sup>3</sup> /h
Gravel	575 kg
Size	48"
Diameter	1260 mm
Weight	246 kg
Filter area	1.13 m <sup>2</sup>
Max flow rate	79 m <sup>3</sup> /h

## PRODUCT INFORMATION

Equipped with "mushroom" diffusers with vertical openings of 0.35mm.  
For filtration stations, stations on skid and electronic controllers (AC or DC) please consult with

us.

Flushing: 60 seconds and up to 75% of the flow is needed for flushing. Flushing is activated by the electronic controller once the pressure loss ( $\Delta P$ ) across the filter has reached the preset value or time setting.

Filtration size: this is influenced by the flow velocity through the filter. Normal design velocity should be 65 - 70 m/hour through the tank.

Media: the gravel media for the filters should be in a layer of precisely 40 cm depth.

Applications: primary filter installed at the main control head, ideal for waters with high contamination of organic material and/or algae. If you need a flanged connection, you can order 3" quick flange for 30" and 36". For 48" you need a 4" quick flange.

- Supplied with connection victaulic to flange.

## Last modified date: 06/11/2025

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)

<http://www.bosta.com>