

**Deepbed filter polyester  
gelcoated 2" male thread  
2,5bar white type with 6-way  
valve ø950mm (7017127)**



# TECHNICAL SPECIFICATIONS


Colour	white
Material	polyester gelcoated
Connection	male thread
Pressure	2,5 bar
Max. temp.	42 °C
Size	2"
Diameter	950 mm
Weight	65 kg
Sand	920 kg
Filter area	0.71 m <sup>2</sup>
Max flow rate	35 m <sup>3</sup> /h
Max. pool vol.	180 m <sup>3</sup>

# DIMENSIONS

A	1750 mm
B	950 mm
C	1168 mm

D

1100 mm



## PRODUCT INFORMATION

This laminated deep bed filter is made with a special reinforced polyester and is UV resistant due to an external gelcoat finish. The increased depth of filter media allows enhanced levels of filtration.

- Made in Italy
- Non corrosive gelcoat fibreglass tank
- Smooth finish
- Transparent lid provides clear view of filter media
- Pressure gauge
- Limit value of backwash  $\geq 0,5$  kpa

**Last modified date: 12/02/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>