Rain Bird Controller plastic 24VAC white type ILX-IVM PEU 240 stations (7028618)



RAIN BIRD



TECHNICAL SPECIFICATIONS

Colour	white
Туре	ILX-IVM
Material	plastic
Voltage	24VAC
Height	364 mm
Туре	PEU
Number of Stations	240

PRODUCT INFORMATION

Rain Bird's new ESP-LX-IVM 2-Wire System comes with the new Integrated Valve Module (IVM). Flow sensor inputs: up to 5 in the LX-IVM and up to 10 in the LX-IVM Pro.

This "smart solenoid" stays in constant communication with the controller, providing efficient irrigation and advanced diagnostics.

Up to four 2-Wire paths can be connected, plus flow sensing and flow management tools. Only half the number of wire splices are needed, improving installation costs and reliability. A 2-Wire path must be surge protected and grounded every 150m or every 15 devices, whichever is smaller. The IVM-SD Line Surge Protector is used for this purpose. Wire connectors included; Languages available: EN, ES, FR, DE, IT, PT.

Last modified date: 06/11/2025

Bosta UK Ltd. Reflection House Olding Road



Bury St. Edmunds Suffolk IP33 3TA T +44 (0) 1284 716580 E enquiries@bosta.co.uk http://www.bosta.com

