

NaanDan Button dripper
plastic 4 mm x 4/7 mm push-in
x barbed 4ltr/h grey/black type
Click Tif, PC CNL (7020709)



NaanDan
by Rivulis

TECHNICAL SPECIFICATIONS

Type	Click Tif, PC CNL
------	-------------------

Material	plastic
----------	---------

Connection	push-in x barbed
------------	------------------

Opening pressure	0,8 - 0,3 bar
------------------	---------------

Rec. press.	1 - 4 bar
-------------	-----------

Colour	grey/black
--------	------------

Flow	4 ltr/h
------	---------

Size	4 mm x 4/7 mm
------	---------------

PRODUCT INFORMATION

The ClickTif CNL (Compensated Non-Leakage) on-line button dripper prevents the system from draining which reduces the filling time of the system and allows all plants to receive the same amount of water.

Opening Pressure: 0.8 bar.

Closing Pressure: 0.3 bar.

Pressure Regulating Range: 0.5 - 4.0 bar; Minimum Working Pressure: 1.0 bar.

Minimum pressure at lateral end: 0.8 bar; Lateral Length exceeding 800m is not recommended.

For fitting into PE40 pipe, punch 3mm hole.

Recommended filtration: 130 micron.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal for pulse irrigation in crops growing in tunnels or greenhouses such as strawberries, peppers, tomato, cucumber, raspberries, eggplants, etc.

Last modified date: 06/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>