

**NaanDan Drip irrigation hose**  
**PE 16 mm x 1,0 mm 39mil 4bar**  
**130micron 1,6ltr/h 50cm black**  
**500m type Amnon PC CNL**  
**(7020662)**



**NaanDan**  
by Rivulis

# TECHNICAL SPECIFICATIONS

Colour	black
Type	Amnon PC CNL
Material	PE
Filtration	130 micron
Filtration	120 mesh
Flow	1,6 ltr/h
Opening pressure	1 bar
Pressure	4 bar
Rec. press.	1 - 4 bar
Size	16 mm
Length	500 m
Inner ø	14 mm
Max. Length	220 m
Dripper spacing	50 cm
Wall thickness	39 mil
Wall thickness	1,0 mm

# PRODUCT INFORMATION

The Amnon CNL (Compensated Non-Leakage) flat dripper prevents the system from draining which reduces the filling time of the system and allows all plants to receive the same amount of water.

Opening Pressure: 1.0 bar.

Closing Pressure: 0.2 bar.

Pressure Regulating Range: 1.0 - 4.0 bar.

Recommended filtration: 130 micron.

Maximum Lateral Length at 0% slope.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal for pulse irrigation in crops growing in bags with soilless media such as strawberries.

**Last modified date: 06/11/2025**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>