

**NaanDan Button dripper
plastic 4/7 mm push-in x
barbed 1,3ltr/h grey/green
type Click Tif, PC (7026014)**



NaanDan
by Rivulis

TECHNICAL SPECIFICATIONS

Type	Click Tif, PC
Material	plastic
Connection	push-in x barbed
Opening pressure	0,8 - 0,3 bar
Rec. press.	1 - 4 bar
Colour	grey/green
Flow	1,3 ltr/h
Size	4/7 mm

PRODUCT INFORMATION

Click Tif PC (Pressure Compensated) on-line button dripper. Pressure Regulating Range: 0.5 - 4.0 bar; Minimum Working Pressure: 1.0 bar. Minimum pressure at lateral end: 0.5 bar; Lateral Length exceeding 800m is not recommended. Recommended filtration: 130 micron. For fitting into PE40 pipe, punch 3mm hole. Coefficient of manufacturing Variation (CV): 3%. Application: ideal dripper for crops in uneven terrains where pressure differences are too big and using the CNL type is not possible due to its opening/closing pressure range. The PC type will open at lower pressure and keep open at higher pressures.

Last modified date: 06/11/2025

Bosta UK Ltd.
Reflection House
Olding Road

Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>