

DAB Multi-stage centrifugal pump stainless steel 304 1" female thread x male thread 230VAC green self priming with press control type EUROINOX 40/30 Control D-CERT - 1.5 bar pressure



TECHNICAL SPECIFICATIONS

Colour	green
Material	stainless steel 304
Material impeller 1	technopolymer
Model	self priming with press control
Connection	female thread x male thread
Voltage	230VAC
Press	1 "
Suction	1 "
Type	EUROINOX 40/30 Control D-GSET adjustable + pressure gauge
Output Power	1,36 HP
MWC	59 m
Size	1"
Power	1 kW
Max flow rate	7.2 m ³ /h
BEP Capacity	5.4
BEP Head	34.7

DIMENSIONS

Cb-1 143 mm

Cl-1 166 mm

G-1 111 mm

H 193 mm

L 439 mm



Mr 241 mm

O 9 mm

W-1 174 mm

ØDi-1 1 "

ØDi-2 1 "



PRODUCT INFORMATION

Supplied with cable, ready to use.

Last modified date: 09/05/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>