NaanDan Drip irrigation hose PE 16 mm x 1,2 mm 47mil 4bar 130micron 1,6ltr/h 33cm brown 100m type TurfDrip Sub Surface (7030182)



NaanDan by Rivulis



TECHNICAL SPECIFICATIONS

Colour	brown
Туре	TurfDrip Sub Surface
Material	PE
Filtration	130 micron
Length	100 m
Inner ø	13,6 mm
Opening pressure	0,5 bar
Dripper spacing	33 cm
Pressure	4 bar
Rec. press.	0,5 - 4 bar
Wall thickness	47 mil
Wall thickness	1,2 mm
Flow	1,6 ltr/h
Size	16 mm
Max. Length	125 m



PRODUCT INFORMATION

The NaanDan TurfDrip with Amnon PC AS dripper is ideal for commercial drip irrigation on ground cover, dense plantings, hedge rows and trees.

AS stands for Anti-Syphon which allows you to install this dripline above and under the ground. The flat in-line Amnon AS dripper comes with an anti root design which prevents roots from entering the dripper labyrinth and clogging it.

The TurfDrip special material gives it additional flexibility in order to avoid kinds in the coils before and during installation.

Brown coils come packed in plastic foil which allows you to save any remaining drip hose in its original packaging.

Pressure Regulating Range: 0.5 - 4.0 bar. Recommended Filtration: 130 micron.

Last modified date: 08/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

