

**Profec Water meter dry cast
iron DN50 DIN flange 10bar
0,01A 15m³/h 24V blue
LXLC/FX type Woltman
horizontal with pulse (7019374)**



TECHNICAL SPECIFICATIONS

Colour	blue
Type	Woltman
Material	cast iron
Model	LXLC/FX
Material flange	cast iron
Material seal	rubber reinforced with nylon
Connection	DIN flange
Pulse	100 ltr
Type	horizontal with pulse
Voltage	24V
Pressure	10 bar
Max. temp.	40 °C
Capacity	25 m ³ /h
Capacity Qmax	30 m ³ /h
Capacity Qn	15 m ³ /h
Size	DN50
Q1 ISO 4064 (2005)	0.5 m ³ /h

Q3 ISO 4064 (2005)	25 m ³ /h
Q4 ISO 4064 (2005)	31.3 m ³ /h
Min. reading	0.0002 m ³ /h
Max. reading	999.999 m ³ /h
Length	200 mm
Diam.	2 "
PCD	125 mm

DIMENSIONS

H	261 mm
Install. length	200
PCD	125 mm

PRODUCT INFORMATION

Output signal: Parallel reed contact (3 wire)

Last modified date: 06/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds

Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>