

**Rain Bird Drip irrigation hose
PE 16 mm x 1,2 mm 4,1bar
125micron 2,3ltr/h 33cm
brown 100m type PC inline XF-
D (7021528)**



RAIN BIRD

TECHNICAL SPECIFICATIONS

Colour brown

Type PC inline XF-D

Material PE

Filtration 125 micron

Inner ø 13,6 mm

Opening pressure 0,58 bar

Maximum ambient temperature 51,7 °C

Pressure 4,1 bar

Max. temp. 38 °C

Rec. press. 0,58 - 4,1 bar

Wall thickness 1,2 mm

Flow 2,3 ltr/h

Size 16 mm

Length 100 m

Max. Length 147 m

Dripper spacing 33 cm

PRODUCT INFORMATION

The Rain Bird Drip irrigation hose, type PC inline XF-D is ideal for drip irrigation on ground cover, dense plantings, hedge rows, trees and in many other applications.

The brown XF-D drip hose can be fitted with the XF insert and lock type fittings.

The XF-D drip hose pressure compensated range goes from 1.0 up to 3.8bar.

The XF-D special material gives it additional flexibility in order to avoid kinks in the coils before and during installation.

The benefit of this is to save time and material by allowing tighter turns with less fittings and stakes.

The inline drippers have a protected labyrinth which allow it to control the flow more precisely when compared to a round dripper.

Last modified date: 06/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>