

**PSH Pool pump polypropylene
2" female thread 6,6A 230VAC
black type ND.2 24M (7032224)**



 P S H

TECHNICAL SPECIFICATIONS

Colour	black
Shaft	stainless steel 316
Pump body	PP/GF30
Material impeller 1	noryl
Material cover	polycarbonate
Material seal	carbon/ceramic
Connection	female thread
Max. temperature	40 °C
Width	220 mm
Height	288 mm
Frequency	50 Hz
IP value	IP55
Motor RPM	2900
Type	ND.2 24M
Capacity	29,3 m ³ /h
Output Power	1,5 HP
Size	2"

Length 581 mm




Voltage 230VAC

Weight 17.1 kg

Power 1.1 kW

MWC 18

Ampere 6,6 A



PRODUCT INFORMATION

High corrosion-resistant materials and quality manufacture have combined to produce a highly reliable, self priming pool pump for your swimming pool.

Features:

- Connection: female thread
- Self-priming up to 4mwh
- Suitable for operation with salt chlorinators and sea water up to 3,5% (35gr/l)
- High efficiency three phase motor class IE3 according to standard IEC 60034-30-1
- Thermal protection incorporated in single-phase version
- Insulation Class: F
- Protection: IP55
- Motor: 50Hz/2900 rpm with option of 60Hz
- Max water temperature: 40°C
- Interchangeable with PSH ND1 pump

Last modified date: 08/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>