

**Deepbed filter polyester
gelcoated 2" male thread
2,5bar white type with 6-way
valve ø800mm (7017126)**



TECHNICAL SPECIFICATIONS


Colour	white
Material	polyester gelcoated
Connection	male thread
Pressure	2,5 bar
Max. temp.	42 °C
Size	2"
Diameter	800 mm
Weight	52 kg
Sand	675 kg
Filter area	0.5 m ²
Max flow rate	25 m ³ /h
Max. pool vol.	140 m ³

DIMENSIONS

A	1700 mm
B	800 mm
C	1121 mm

D

1060 mm



PRODUCT INFORMATION

This laminated deep bed filter is made with a special reinforced polyester and is UV resistant due to an external gelcoat finish. The increased depth of filter media allows enhanced levels of filtration.

- Made in Italy
- Non corrosive gelcoat fibreglass tank
- Smooth finish
- Transparent lid provides clear view of filter media
- Pressure gauge
- Limit value of backwash $\geq 0,5$ kpa

Last modified date: 12/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>